



MANUAL



AIR

WATER



RETRACTABLE



ELECTRIC



FUEL



FIRE



HOSE REELS

120... FIRE HOSE REELS, RETRACTABLE REELS



121... MANUAL WIND REELS

to

122



122.. ELEC REWI REEL



TRIC ND S

All dimensions and weights are nominal and subject to change.



COMPLETE FIRE HOSE REELS



36mtr x 3/4" size Fire Hose Reel.
Complete with pvc hose and nozzle. Wall mountable configuration and assembly kit.
Product Code: 615-600



25 mtr x 3/4" size Mobile Fire Hose Reel.
Complete with pvc hose and nozzle. Wall mountable and portable options.
Product Code: 615-601

RETRACTABLE HOSE REELS

Air



8 mtr Air Reel Product Code: JAMEC-AIR008

Fitted with 8 mtrs polyurethane braided hose with 1/4" BSP hose fittings and leader hose already pre-fitted. Features auto latching system, adjustable hose stopper. Steel bracket allows the reel to pivot 180 Deg.



20 mtr Air Reel Product Code: JAMEC-AIR020

Fitted with 20 mtrs braided hose with 1/4" BSP hose fittings and leader hose already pre-fitted. Features unique hose layering system which prevents tangles and jamming in the reel, adjustable hose stopper, impact resistant case. Ideal for industrial and automotive sites, mobile and home workshops.

Water



20 mtr Water Reel Product Code: JAMEC-WATER020

Fitted with 20 mtrs braided hose with hose fittings and nozzle. Features unique hose layering system which prevents tangles and jamming in the reel, adjustable hose stopper, impact resistant case. Ideal for garden use and a wide range of other domestic/industrial purposes.



MANUAL HOSE REELS

FUEL HOSE REEL:

Product Code: 982-REEL



Specifications:

Standard Hose Reels: For hoses sizes 20mm - 40mm I.D.

Cheekplates: 575mm. Made with rolled edges from heavy gauge steel sheet.

Drums with full flow hub assemblies: Fabricated from heavy gauge steel sheet with standard diameter of 305mm. Drum width vary according to desired drum capacity.

Rewind Mechanisms: Direct drive hand rewind is standard for hose sizes to 76.2mm. Geared hand rewind available as an alternative.

Electrically powered rewind operates through positive sprocket and chain drives. Hydraulic powered rewind operates through direct drives, although sprocket and chain drives can fitted as an alternative.

For emergency use, auxiliary geared hand crank can be fitted.

Standard assembly for rewind mechanism at right-hand side facing reel, but mechanism can be mounted on left hand side if required.

Mounting Frames: Standard dimension frames are assembled to all standard hose reels.

Fluid Temperature: up to 100o C

Combined Swivel Joint-Bearing: Specially sealed for long life at high pressures. Available in the various materials to suit specific duties including gunmetal, stainless steel, aluminium, steel and hard chromed-steel.



40 mtr Air Reel

Product Code: JAMEC-AIR40

Fitted with 40 mtrs polyurethane braided kink resistant hose with 1/4" BSP hose fittings and leader hose already pre-fitted. Features 360 Deg rotary base with a fold away winding system. Ideal for industrial and automotive sites and home workshops.

A Frame Hose Reel



REEL FEATURES:

- Powder Coated Frame
- Brass swivel Hostails

| Product Code | Hose I/D | Hose Capacity |
|--------------|----------|---------------|
| REEL-012-030 | 12mm | 30mtr |
| REEL-012-050 | 12mm | 50mtr |
| REEL-020-036 | 19mm | 36mtr |
| REEL-020-050 | 19mm | 50mtr |
| REEL-020-080 | 19mm | 80mtr |
| REEL-025-020 | 25mm | 20mtr |
| REEL-025-036 | 25mm | 36mtr |
| REEL-025-060 | 25mm | 60mtr |





Heavy Duty Aluminium Reel

| Product Code | Hose I/D | Hose Capacity | Dimensions |
|---------------|----------|---------------|------------------|
| REELEZY-1930 | 19mm | 30mtr | 580W, 530D, 500H |
| REELEZY-1950 | 19mm | 50mtr | 710W, 530D, 500H |
| REELEZY-2530 | 25mm | 30mtr | 710W,530D,500H |
| REELEZY-1970 | 19mm | 70mtr | 800W, 670D, 550H |
| REELEZY-2550 | 25mm | 50mtr | 800W,670D, 550H |
| REELEZY-25100 | 25mm | 100mtr | 800W, 840D, 870H |

REEL FEATURES:

- Aluminium construction.
- Heavy duty, large capacity
- Bronze bearings, greaseable bronze swivel
- Available with or without roller guides
- Can be custom made to your particular needs

ELECTRIC REWIND REELS



| Product Code | Hose I/D | Hose Capacity | Dimensions | Voltage |
|---------------|----------|---------------|------------------|---------|
| REEL-30X1912E | 19mm | 30mtr | 710W, 530D, 550H | 12 |
| REEL-50X1912E | 19mm | 50mtr | 840W, 530D, 550H | 12 |
| REEL-30X2512E | 25mm | 30mtr | 840W,530D,550H | 12 |
| REEL-30X1924E | 19mm | 30mtr | 710W, 530D, 550H | 24 |
| REEL-50X1924E | 19mm | 50mtr | 840W, 530D, 550H | 24 |
| REEL-30X2524E | 25mm | 30mtr | 840W, 530D,5500H | 24 |

REEL FEATURES:

- Aluminium construction.
- Positive gear drive
- Greaseable bronze swivel
- Available with or without roller guides

Note: Hose not included, for illustration purposes only



| Product Code | Hose I/D | Hose Capacity | Dimensions | Voltage |
|---------------|----------|---------------|------------------|---------|
| REEL-70X1912E | 19mm | 70mtr | 900W, 670D, 550H | 12 |
| REEL-50X2512E | 25mm | 50mtr | 900W, 670D, 550H | 12 |
| REEL-70X1924E | 19mm | 70mtr | 900W, 670D,550H | 24 |
| REEL-50X2524E | 25mm | 50mtr | 900W, 670D, 550H | 24 |

REEL FEATURES:

- Aluminium construction
- Heavy duty, large capacity
- Automatic rewind available
- Can also be air or hydraulically powered



