

MULTI PURPOSE



WATER




AIR



WELDING



FUEL



AUTOMOTIVE

THERMOID EXTRUDED RUBBER HOSE


194....	G.P. MULTIPURPOSE VERSICON	
195....	PUMPFLEX-2 VALUFLEX BLACK AIRFLEX	 
196....	CAR HEATER FUEL LINE AIR BRAKE	 
197....	FARM TANK ANTI-STATIC HERCULES 500 DARI-PREEN	 
198....	TWIN WELD GAS SINGLE-WELD GAS	

All dimensions and weights are nominal and subject to change



HBD EXTRUDED

GP MULTIPURPOSE:



General purpose oil resistant hose. The cover has good resistance to ozone, weathering, abrasion and oil. It is non-conductive and offers medium-high oil resistance

Tube: Black Nitrile blend RMA Class A.

Cover: Red Nitrile blend RMA Class B.

Reinforcing: Spiral polyester yarn.

Temperature Range: -29°C to 71°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E01-006	6.35	12.70	250	0.12	213
E01-008	7.94	15.88	250	0.21	213
E01-010	9.53	18.30	250	0.25	213
E01-012	12.70	22.40	250	0.36	213
E01-016	15.88	25.40	300	0.42	213
E01-020	19.05	29.50	250	0.54	213
E01-025	25.40	36.60	250	0.73	213
E01-032	31.75	45.24	250	1.16	152
E01-038	38.10	51.60	250	1.34	122

VERSICON:



Premium quality fuel* and oil resistant hose. The non-conductive cover has good resistance to ozone, weathering, abrasion and oil.

Tube: Black Nitrile Class A.

Cover: Red NBR/PVC Class A non conductive.

Reinforcing: Spiral polyester yarn.

Temperature Range: -29°C to 82°C


Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E08-010	9.53	18.03	300	0.27	213
E08-012	12.70	22.40	300	0.37	213
E08-020	19.05	29.50	300	0.62	213
E08-025	25.40	38.10	300	0.94	213

*Note: This product is not suitable for unleaded fuel.



HBD EXTRUDED

PUMPFLEX 2:



This rugged one wire braid hose has excellent dimensional stability. This construction eliminates elongation, expansion and contraction under pressure. Pumpflex 2 is UL listed.

Tube: Black Nitrile/PVC, RMA Class A.

Cover: Black Thermalon, U/L approved Class B.

Reinforcing: Steel wire braid.

Temperature Range: -40°C to 82°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E15-016	15.88	26.19	200	0.60	152
E15-020	19.05	28.58	200	0.65	152
E15-025	25.40	38.10	150	1.03	152

VALUEFLEX BLACK:



Economical general purpose hose for various industrial and agricultural applications. Weather, ozone and abrasion resistant cover.

Tube: Black EPDM.

Cover: Black EPDM.

Reinforcing: Spiral polyester yarn.

Temperature Range: -40°C to 93°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E03-012	12.70	22.40	200	0.36	213
E03-020	19.05	29.50	200	0.54	213
E03-025	25.40	36.60	200	0.73	213

AIRFLEX:



Premium quality pneumatic air tool hose for use when lubricating with oil mist through air lines. Weather, ozone and abrasion resistant cover.

Tube: Oil Resistant EPDM Tube

Cover: Yellow EPDM.

Reinforcing: Spiral polyester yarn.

Temperature Range: -40°C to 93°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E02-006	6.40	16.00	300	0.22	213
E02-010	9.50	18.30	300	0.27	213
E02-012	12.70	22.40	300	0.37	213
E02-020	19.10	29.50	300	0.55	213
E02-025*	25.40	38.10	300	0.91	213

* Golden Airflex

Tube: Black NBR, RMA Class A

Cover: Yellow NBR,PVC RMA Class A

Temperature Range: -29°C to 82°C

Non-Conductive



HBD EXTRUDED

CAR HEATER:



A quality vehicle heater hose. Resistant to common coolant solutions.

Tube: Black EPDM.

Cover: Black EPDM.

Reinforcing: Spiral polyester yarn.

Temperature Range: -40°C to 93°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E05-012	12.70	19.60	35	0.24	213
E05-016	15.90	22.40	35	0.30	213
E05-020	19.10	25.90	35	0.34	213

FUEL LINE:



Premium automotive fuel line which meets SAE30R7 specifications. Ozone, oil, grease and abrasion resistant cover.

Tube: Black NBR, RMA Class A.

Cover: Black NBR/PVC, RMA Class B.

Reinforcing: Spiral polyester yarn.

Temperature Range: -34°C to 125°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E06-005	4.76	10.40	35	0.10	213
E06-006	6.40	12.70	35	0.13	213
E06-008	7.90	14.20	35	0.16	213
E06-010	9.50	16.00	35	0.18	213
E06-012	12.70	19.20	35	0.23	213

AIR BRAKE:



Designed for conveying air in truck brake systems. Meets DOT FMVSS 106 and SAE J1402A requirements.

Tube: Black EPDM, RMA Class C.

Cover: Black EPDM, RMA Class C.

Reinforcing: Spiral polyester yarn.


Temperature Range: -40°C to 93°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E15-010	9.50	19.10	300	0.25	152
E15-012	12.70	22.40	300	0.30	152



HBD EXTRUDED

FARM TANK ANTI STATIC:



Farm Tank hose is designed for gravity flow diesel, oil, kerosene and gasoline delivery applications. An anti-static wire is incorporated. The cover is oil and abrasion resistant.

Tube: Black NBR, RMA Class A.

Cover: Black NBR/PVC RMA Class A.

Reinforcing: Spiral polyester yarn.

Temperature Range: -29°C to 71°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E07-020	19.10	26.90	60	0.43	213
E07-025	25.40	35.10	60	0.67	213

NOTE: This hose is not suitable for use with unleaded fuel.

HERCULES 500:



Premium heavy duty air and water delivery hose for use in the mining and industrial sectors. MSHA approved non-conductive cover.

Tube: Black NBR/PVC, RMA Class A.

Cover: Yellow carboxylated Nitrile Class A non-conductive.

Reinforcing: Spiral polyester yarn.

Temperature Range: -40°C to 100°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E09-010	9.50	19.10	500	0.31	213
E09-012	12.70	23.10	500	0.36	213
E09-020	19.10	30.20	500	0.54	213
E09-025	25.40	38.10	500	0.76	213

DARI-PREEN:



Premium washdown hose for use in the dairy and food processing industries. Weather, ozone and abrasion resistant cover.

Tube: Black EPDM.

Cover: White EPDM.

Reinforcing: Spiral polyester yarn.

Temperature Range: -40°C to 82°C

Product Code	I.D. (mm)	O.D. (mm)	W.P (Psi)	Weight (Kg/mt)	Reel Length (mt)
E11-012	12.70	23.10	250	0.43	213
E11-020	19.10	31.80	200	0.74	213



HBD EXTRUDED

TWIN WELD GAS:



Product Code	I.D. (mm)	O.D. (mm)	W.P (psi)	Weight (kg/mt)	Colour	Reel Length (mt)
ME16A-005	5.0	12.0	304	0.27	Blu/Red	100
ME16L-105	5.0	12.0	304	0.27	Blu/Org	100

For use on gas equipment in the construction and manufacturing industries. Suitable for use with reusable gas fittings.

Tube: Black Nitrile Class B.

Cover: Blue/Red (Oxy/Acc) Nitrile Class B.
Blue/Org (Oxy/LPG) Nitrile Class B.

Reinforcing: HD = 2 spiral polyester yarn.

Oxygen and acetylene brass reusable fitting, suitable for use on the "Twin-Weld" and "Single-Weld" gas hoses. Other adaptors also available on request.



Product Code	Hose I.D. (mm)	Use (gas)
599-LP240	5.0	Oxy.
599-LP112	5.0	Acc.
599-LP265	5.0	Joiner

SINGLE WELD GAS:



Product Code	I.D. (mm)	O.D. (mm)	W.P (psi)	Weight (kg/mt)	Colour	Reel Length (mt)
ME17-005	5.0	12.0	300	0.14	Blue	100
ME17-010	10.0	17.0	300	0.20	Blue	100
ME18-005	5.0	12.0	300	0.15	Red	100
ME18-010	10.0	17.0	300	0.25	Red	100
ME19-005	5.0	12.0	300	0.15	Orange	100
ME19-010	10.0	18.0	300	0.24	Orange	100

For use on gas equipment in the construction and manufacturing industries. Suitable for use with reusable gas fittings.

Tube: Black Nitrile Class B.

Cover: Blue (Oxy.) Nitrile Class B.
Red (Acc.) Nitrile Class B.
Orange (LPG) Nitrile Class B.

Reinforcing: Spiral polyester yarn.



