

EXHAUST GASKET



Size	Nitrile Sheet Gasket - 60 oC to 90 oC	Reinforced Graphite Gasket with 316 S/S Tanged Insert 200 °C to 459 °C
1/2"	205-015	205-GH015
3/4"	205-020	205-GH020
1"	205-025	205-GH025
1 1/4"	205-032	205-GH032
1 1/2"	205-040	205-GH040
2"	205-050	205-GH050
2 1/2"	205-065	205-GH065
3"	205-080	205-GH080
4"	205-100	205-GH100
5"	205-125	205-GH125
6"	205-150	205-GH150
8"	205-200	205-GH200
10"	205-250	205-GH250
12"	205-300	205-GH300

INSERTION RUBBER & RIBBED



Product Code	Rubber Compound	Thickness (mm)	Plies	Width (Mt...)	Weight (kg/mt)	Roll Lth (mt)
S01-008	Natural	0.8	1	1.20	1.22	10
S01-015	Natural	1.5	1	1.20	2.30	10
S01-030	Natural	3.0	1	1.20	4.57	10
S01-040	Natural	4.5	1	1.20	6.86	10
S01-045	Natural	4.5	2	1.20	6.86	10
S01-060	Natural	6.0	2	1.20	9.14	10
S01-095	Natural	9.5	2	1.20	14.48	5, 10
S02-030	Neoprene	3.0	1	1.20	4.57	10

RIBBED MAT:

Product Code	Rubber Compound	Thickness (mm)	Rib Section	Width (mt)	Weight (kg/mt)	Roll Lth (mt)
S05-1235	Natural	3.0	Fine	1.20	5.67	10
S05-1550	Natural	5.0	Fine	1.50	11.80	10

