

PVC PRESSURE HOSE

PASTORAL



Applications: Dairy, marine and general industry washdown hose.

White in colour. **Temperature:** 0°C to 60°C

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	B.P (P.S.I)	Weight (kg/m)	Coil Length
A06-012	12.5	19.0	175	700	0.20	20, 55, 100, 200
A06-020	19.0	26.5	175	700	0.35	20, 50, 100
A06-025	25.0	34.0	145	580	0.54	20, 30, 50, 55, 100
A06-032	32.0	43.0	145	580	0.82	20, 100


ESTATE BLUELINE



Applications: Heavy-duty industrial, agricultural and marine washdown. **Temperature:** 0°C to 60°C

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	B.P (P.S.I)	Weight (kg/mt)	Coil Lengths
A55-020	19.0	26.0	150	450	0.30	20, 100
A55-025	25.0	33.0	150	450	0.45	20, 100
A55-032	32.0	42.0	150	450	0.78	20, 100
A55-038	38.0	48.0	150	450	0.92	20, 60

TMP II



For the transfer of air, water and petroleum based products. UV stabilised. **Temperature:** 0 °C to 60 °C

Product Code	I.D mm	O.D mm	W.P. P.S.I	B.P. P.S.I.	Weight Kg/mt	Coil Lengths mt
A53-006	6.0	10.8	230	920	0.09	20, 100
A53-008	8.0	13.2	230	920	0.12	20, 100
A53-010	10.0	15.2	230	920	0.15	20, 80
A53-012	12.5	18.9	230	920	0.21	20, 55
A53-016	16.0	22.8	230	920	0.27	20, 100
A53-020	19.0	26.5	230	920	0.35	20, 80
A53-025	25.0	33.0	230	920	0.52	20, 75
A53-032	32.0	41.2	175	700	0.72	20, 60
A53-038	38.0	48.0	145	580	1.15	20, 40

DRINKING WATER HOSE



Applications: For conveying of drinking water. Conforms to AS2070.1 & AS4020 White with blue stripe. **Temperature:** 0 °C to 60 °C

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	B.P (P.S.I)	Weight (kg/mt)	Coil Length
A18-012	12.0	17.0	110	435	0.13	20, 60, 100

CVT



Applications: Non toxic tube suitable for food and beverage transfer. Clear in colour. **Temperature:** 0 °C to 60 °C

* = Calfateria tube

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	B.P (P.S.I)	Weight (kg/mt)	Coil Length
A15-003	3.0	5.0	125	250	0.017	30, 300
A15-004	4.0	7.0	120	230	0.030	30
A15-005	5.0	8.0	115	230	0.040	30, 120
A15-006	6.0	9.0	90	180	0.046	30, 100
A15-008	8.0	11.0	75	150	0.058	30, 150
A15-010	10.0	13.0	60	120	0.070	30, 130
A15-011*	10.0	15.0	90	180	0.128	30, 80, 130
A15-012	12.5	16.5	70	138	0.118	30, 90
A15-016	16.0	20.0	60	120	0.147	30, 60
A15-020	19.0	24.0	50	100	0.220	30, 40, 100
A15-025	25.0	31.0	50	100	0.343	30, 40, 50
A15-032	32.0	38.0	40	80	0.429	30
A15-038	38.0	46.0	40	80	0.686	30



PVC SUCTION HOSE

WHITE SANITATION HOSE



Applications: Plumbing of marine toilets. PVC helix, smooth bore, remains flexible at low temperatures.

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I) @20°C	Vac (mH ₂ O)	Weight (Kg/mt)	Coil Lengths
B52-020	20.0	24.0	50	8	0.30	20
B52-025	25.0	32.0	50	8	0.40	20
B52-038	38.0	45.0	40	8	0.46	20


MARINE FLEX SUCTION HOSE



Applications: Extremely flexible, smooth bore hose for marine water suction. Very tight bending radius without kinking.

Product Code	I.D (mm)	OD (mm)	W.P (P.S.I)	Vac (mH ₂ O)	Weight (kg/mt)	Coil Length
B59-020	19.0	25.0	50	6	0.35	20
B59-025	25.0	31.0	50	6	0.54	20
B59-028	28.0	35.0	40	6	0.54	20
B59-032	32.0	38.0	40	6	0.80	20
B59-038	38.0	45.0	40	6	0.95	20
B59-050	50.0	59.0	40	6	1.10	20

PLUTONE



Applications: Plasticized PVC hose with steel spiral reinforcements. Highly flexible, smooth inside and outside, transparent wall. Resistant to most atmospheric agents and most chemicals. Good abrasion resistance. Meets AS2070 and FDA standards for food contact to 4".

**** Other Sizes also available on request.**

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I) @20°C	Vac (mH ₂ O)	Weight (Kg/mt)	Coil Lengths
B22-006	6.0	12.0	100	9	0.13	60
B22-010	10.0	16.0	100	9	0.16	60
B22-012	12.0	18.0	80	9	0.18	60
B22-016	16.0	22.4	80	9	0.25	60
B22-020	20.0	27.0	70	9	0.35	60
B22-025	25.0	33.0	70	9	0.50	60
B22-032	32.0	41.0	60	9	0.65	60
B22-038	38.0	47.0	60	9	0.80	30
B22-044	45.0	55.0	60	8	1.10	30
B22-050	50.0	60.8	60	8	1.25	30

SUPER E PETROL & OIL



Applications: Highly elastic polymer delivers super flexibility from a heavy walled hose. Specifically designed for the transfer of hydrocarbon based products such as diesel, petrol, oil, greases & lubricants. Also chemical resistant and suitable for water.

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I) @20°C	Vac (mH ₂ O)	Weight (Kg/mt)	Coil Lengths
B05-025	25.0	34.0	90	9	0.53	20, 40
B05-032	32.0	41.0	90	9	0.68	20, 40
B05-038	38.0	48.0	90	9	0.84	20, 40
B05-050	50.0	62.0	70	9	1.30	20, 40
B05-063	63.0	76.0	70	9	1.76	20, 40
B05-075	76.0	90.0	65	9	2.29	20, 40
B05-100	102.0	117.0	50	9	3.33	20

