


MARINE RUBBER HOSE

AUSTRALIA OIL DELIVERY



Medium duty mandrel built delivery hose, for the transfer of petroleum based products with up to 30% aromatic content. **Not recommended for ULP transfer.**

Tube: Black smooth nitrile rubber.
Cover: Black smooth chloroprene rubber.
Reinforcing: Plies of synthetic cord.
Temperature: -15 to +70 degrees Celsius.
Markings: IVG "oil" red stripe, 10 bar W.P.

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/mt)	Coil Lth (mt)
H27-012	13.0	20.0	150	450	0.24	20
H27-020	19.0	27.0	150	450	0.39	20, 60
H27-025	25.0	36.0	150	450	0.52	20, 120
H27-032	32.0	42.0	150	450	0.82	20, 120
H27-038	38.0	48.0	150	450	0.94	20, 120
H27-044	45.0	55.0	150	450	1.01	20
H27-050	51.0	61.0	150	450	1.12	20, 60
H27-057	58.0	70.0	150	450	1.60	20
H27-063	63.5	74.0	150	450	1.46	20, 60
H27-075	76.0	89.0	150	450	2.14	20, 60
H27-090	90.0	105.0	150	450	2.87	20
H27-100	102.0	115.0	150	450	2.97	20, 60

MALMO OIL SUCTION



Tank truck suction and delivery hose, used for transfer of a wide range of petroleum based products with up to 30% aromatic content.

Not recommended for ULP transfer.

Tube: Black smooth nitrile rubber
Cover: Black smooth chloroprene rubber.
Reinforcing: Plies of synthetic cord, steel wire helix.
Temperature: -15 to +70 degrees Celsius.
Markings: IVG "oil" red stripe, 10 bar W.P.

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/mt)	Coil Lth (mt)
H28-020	19.0	30.0	150	450	0.67	20
H28-025	25.0	35.0	150	450	0.79	20, 60
H28-032	32.0	43.0	150	450	1.03	20, 60
H28-038	38.0	49.5	150	450	1.33	20, 60
H28-044	45.0	57.0	150	450	1.57	20
H28-050	51.0	63.0	150	450	1.83	20, 60
H28-057	58.0	71.0	150	450	2.45	20
H28-063	63.5	78.0	150	450	2.78	20, 60
H28-075	76.0	89.0	150	450	2.92	20, 60
H28-090	90.0	106.0	150	450	3.82	20
H28-100	102.0	119.0	150	450	4.83	20, 60
H28-114	114.0	132.5	150	450	6.24	20
H28-125	125.0	145.0	150	450	7.52	20

IVALO OIL SUCTION & DELIVERY



Flexible rubber hose with corrugated cover for extra flexibility, suited to convey a wide range of petroleum based products with up to 30% aromatic content. Suitable for suction (vacuum 0.5 bar) and delivery.

Tube: Black smooth nitrile rubber
Cover: Black Corrugated CR rubber
Reinforcing: Plies of Synthetic cord, steel wire helix
Temperature: -30 to + 120 Degrees Celsius
Markings: IVG red stripe

Product Code	I.D. (mm)	W.P. (psi)	B.P. (psi)	Bend Radius (mm)	Weight (Kg/mt)	Coil Lth (mt)
H29-020	19	75	225	50	0.40	60
H29-022	22	75	225	60	0.45	60
H29-025	25	75	225	67	0.50	60
H29-028	28	75	225	75	0.55	60
H29-032	32	75	225	85	0.62	60
H29-035	35	75	225	95	0.67	60
H29-038	38	75	225	105	0.70	60
H29-042	42	75	225	120	0.76	60
H29-045	45	75	225	130	0.81	60
H29-051	51	75	225	150	1.01	60

SUPER FLEXIBLE



MARINE RUBBER HOSE

ETNA L/D



Light duty mandrel built suction and delivery hose, specially designed for conveying wet exhaust fumes in the marine industry. Corrugated outer cover for extra flexibility.

Tube: Black smooth CR rubber.

Cover: Black corrugated CR rubber.

Reinforcing: Plies of synthetic cord, steel wire helix.

Temperature: -10 to +100 degrees Celsius.

Markings: IVG blue stripe.

*Other sizes are available, please call us for information.

APPROVED TO:

LLOYD'S APPROVAL: No: 99/0169

NMA NBS MC9: No COL98.

FLAME RESISTANT

Product Code	I.D. (mm)	Bend Radius (mm)	W.P (psi)	B.P (psi)	Weight (kg/mt)	Coil Lth (mt)
H23-025	25.0	110	25	75	0.48	60
H23-028	28.0	120	25	75	0.78	3
H23-032	32.0	130	25	75	0.59	60
H23-038	38.0	150	25	75	0.68	60
H23-045	45.0	170	25	75	0.79	60
H23-050	51.0	180	25	75	0.98	60
H23-057	58.0	190	25	75	1.10	60
H23-060	60.0	190	25	75	1.14	60
H23-063	63.5	200	25	75	1.20	60
H23-070	70.0	250	25	75	1.32	60
H23-075	76.0	380	25	75	1.35	60
H23-090	90.0	330	25	75	1.58	60
H23-100	102.0	410	25	75	1.90	60
H23-114	114.0	485	25	75	2.30	60
H23-127	127.0	560	25	75	2.39	20
H23-152	152.0	680	20	60	2.97	10
H23-203	203.0	995	15	45	4.53	10

MARINE FILL



Application: SAE J1527 Type A2, ISO 7840 and CE Fuel fill hose is for marine gasoline tanks. It is the connection from the boat's fuel fill port to fuel tank.

Tube: Chemigum synthetic rubber.


Reinforcement: Spiral Piled synthetic fabric with wire helix.

Cover: Chemivic synthetic rubber (wrapped impression)

Temperature: Ambient

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	Safety Factor	Weight (Kg/mt)	Coil Lengths (mt)
H71-020	19.0	29.4	100	4:1	0.51	15.25
H71-025	25.0	38.1	100	4:1	0.64	15.25
H71-032	32.0	47.3	100	4:1	0.97	15.25
H71-038	38.0	58.3	100	4:1	1.43	15.25
H71-050	50.0	61.5	50	4:1	1.52	15.25
H71-060	60.0	71.0	50	4:1	1.78	15.25

MARINE FUEL



Application: USCG/SAE J1527 Type A1 and ISO 7840-A1 Fuel Feed / Vent hose for marine gas tanks. For fuel feed and vent application of marine craft.

Tube: Chemigum synthetic rubber.

Reinforcement: Spiral synthetic yarn.

Cover: Chemivic synthetic rubber

Temperature: Ambient

Product Code	I.D (mm)	O.D (mm)	W.P (P.S.I)	Safety Factor	Weight (Kg/mt)	Coil Lengths (mt)
H72-006	6.0	16.5	49	4:1	0.254	61.0
H72-008	8.0	18.0	49	4:1	0.283	61.0
H72-010	10.0	19.8	49	4:1	0.298	61.0
H72-012	12.0	22.8	36	4:1	0.388	61.0
H72-016	16.0	25.8	36	4:1	0.522	61.0



MARINE RUBBER HOSE

YORK RADIATOR



Mandrel built rubber delivery hose, recommended for handling hot water, antifreeze etc.. in cooling system.

Tube: Black smooth EPDM rubber.

Cover: Black smooth EPDM rubber.

Reinforcing: Plies of synthetic cord.

Temperature: -40 to +100 degrees Celsius.

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	Weight (kg/mt)	Unit Lth (mt)
H15-012	13.0	19.0	45	0.20	1.0
H15-016	16.0	23.0	45	0.24	1.0
H15-019	19.0	27.0	45	0.31	1.0
H15-022	22.0	30.0	45	0.32	1.0
H15-025	25.0	33.5	45	0.35	1.0
H15-028	28.0	36.5	45	0.40	1.0
H15-030	30.0	38.0	45	0.52	1.0
H15-032	32.0	40.0	45	0.55	1.0
H15-035	35.0	43.0	45	0.60	1.0
H15-038	38.0	46.0	45	0.73	1.0

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	Weight (kg/mt)	Unit Lth (mt)
H15-040	40.0	49.0	45	0.77	1.0
H15-042	42.0	51.0	45	0.80	1.0
H15-045	45.0	54.0	45	0.97	1.0
H15-048	48.0	57.0	45	1.02	1.0
H15-051	51.0	61.0	45	1.10	1.0
H15-055	55.0	65.0	45	1.20	1.0
H15-058	58.0	67.0	45	1.23	1.0
H15-060	60.0	70.0	45	1.25	1.0
H15-063	63.5	74.0	45	1.38	1.0
H15-065	65.0	75.0	45	1.40	1.0
H15-070	70.0	80.0	45	1.45	1.0
H15-073	73.0	83.0	45	1.51	1.0
H15-076	76.0	86.0	45	1.55	1.0
H15-080	80.0	90.0	45	1.98	1.0
H15-083	83.0	93.0	45	2.04	1.0
H15-090	90.0	100.0	45	2.15	1.0
H15-102	102.0	112.0	45	2.32	1.0
H15-114	114.0	127.0	45	2.40	1.0
H15-127	127.0	140.0	45	2.48	1.0
H15-140	140.0	152.0	45	2.92	1.0
H15-152	152.0	167.0	45	3.36	1.0

TORONTO WATER SUCTION



Heavy duty mandrel built water suction and discharge hose. Used in pumping applications where a rugged hard wearing hose is required.

Tube: Black smooth SBR rubber.

Cover: Black smooth EPDM rubber

Reinforcing: Plies of synthetic cord, steel wire helix.

Temperature: -35 to +70 degrees Celsius.

Markings: IVG "water" green stripe, 10 bar W.P.

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/mt)	Coil Lth (mt)
H14-020	19.0	29.0	150	450	0.63	20
H14-025	25.0	35.0	150	450	0.82	20, 60
H14-032	32.0	42.0	150	450	0.98	20
H14-038	38.0	47.0	150	450	1.28	20, 60
H14-050	51.0	63.0	150	450	1.74	20, 60
H14-063	63.5	75.0	150	450	2.39	20
H14-075	76.0	87.0	150	450	2.53	20, 60
H14-090	90.0	104.0	150	450	3.92	20
H14-100	102.0	114.0	150	450	4.60	20, 60

MONTREAL WATER DELIVERY / 10 BAR



Medium duty mandrel built water discharge hose, widely used by industry, construction sites etc.

Tube: Black smooth SBR rubber.

Cover: Black smooth EPDM rubber

Reinforcing: Plies of synthetic cord.

Temperature: -35 to +70 degrees Celsius.

Markings: IVG "water" green stripe, 10 bar W.P.

Product Code	I.D. (mm)	O.D. (mm)	W.P. (psi)	B.P. (psi)	Weight (kg/mt)	Coil Lth (mt)
H04-012	13.0	20.0	150	450	0.23	20
H04-020	19.0	26.0	150	450	0.29	20
H04-025	25.0	33.0	150	450	0.46	20
H04-032	32.0	42.0	150	450	0.77	20
H04-038	38.0	48.0	150	450	0.85	20, 120
H04-044	45.0	55.0	150	450	1.01	20
H04-050	51.0	61.0	150	450	1.12	20, 120
H04-063	63.5	75.5	150	450	1.70	20, 60
H04-075	76.0	87.0	150	450	1.79	20, 120
H04-090	90.0	102.0	150	450	2.60	20
H04-100	102.0	115.0	150	450	4.07	20



MARINE RUBBER HOSE

GOODYEAR CAR HEATER HOSE (SAE30R3)



Application: A high quality, economically priced hose. Produced with a tough versigard tube and cover to resist heat, ozone and antifreeze present in today's automobiles. Meets SAE30R3 requirements for burst pressure and temperature requirements.

Tube: Black versigard

Reinforcement: Synthetic textile

Cover: Black versigard

Temperature: Up to 121°C

PACKAGING: Soft Reels maximum 3pcs, increments

Product Code	I.D (mm)	O.D (mm)	W.P (Psi)	Weight (Kg/m)
E61-012	12.70	19.6	65	.22
E61-016	15.88	23.1	65	.32
E61-019	19.05	26.7	65	.37

GOODYEAR WINGFOOT



Application: A good quality, economical, general purpose hose for industrial air service, compressor lines, pneumatic tools, low pressure spray, and many other applications where the need for oil resistance is moderate. Non conductive.

Tube: Chemigum®, RMA Class A (High Oil Resistance)

Reinforcement: Spiral synthetic yarn

Cover: Blue, Black or Red Chemivic®, RMA Class B (Medium-High Oil Resistance)

Temperature: -29°C to 100°C

Product Code	I.D (mm)	O.D (mm)	W.P (Psi)	Weight (Kg/m)
E51-006	6.35	13.5	200	0.15
E51-008	7.94	15.9	200	0.21
E51-010	10.00	17.5	200	0.23
E51-012	12.70	21.4	200	0.32
E51-016	15.88	25.4	200	0.43
E51-020	19.05	28.6	200	0.50
E51-025	25.40	37.3	200	0.80
E51-032	31.75	45.6	250	1.11
E51-038	38.10	53.2	250	1.44

GOODYEAR FUEL HOSE (SAEJ30R7)



Application: Especially for later model vehicle applications, with high under the bonnet temperatures. The hysunite hose cover is oil and petrol resistant and withstands exposure to fuel, vapor, moisture and heat up to 121 oC. The chemigum rubber tube is specially compounded to resist petrol, oil, diesel and other fuels.

Tube: Chemigum (Black)

Reinforcement: Synthetic Textile

Cover: Hysunite (Black)

Temperature: - 40 °C to 121 °C

Packaging: Soft Reels maximum three piece, increments

Product Code	I.D (mm)	O.D (mm)	W.P (Psi)	Weight (Kg/m)
E62-005	4.76	10.3	150	.09
E62-006	6.35	12.7	150	.14
E62-008	7.94	14.3	150	.17
E62-010	9.53	15.9	150	.18
E62-012	12.70	19.8	150	.26

HBD THERMOID FUEL LINE



Premium automotive fuel line which meets SAE30R7 specifications. Ozone, oil, grease and abrasion resistant cover.

Tube: Black Nitrile Class A.

Cover: Black Hypalon Class B

Reinforcing: Two spiral polyester yarn.

Applications: Fuel and oil transfer.

Product Code	I.D. (mm)	O.D. (mm)	W.P (psi)	Weight (kg/mt)
E06-005	5.0	10.3	150	0.12
E06-006	6.0	12.5	150	0.14
E06-008	8.0	14.3	150	0.17
E06-010	10.0	15.9	150	0.20
E06-012	12.5	19.08	150	0.24

HBD THERMOID CAR HEATER



A quality vehicle heater hose. Resistant to common coolant solutions.

Tube: Black EPDM.

Cover: Black EPDM.

Reinforcing: Two spiral polyester yarn.

Applications: Vehicle heater hose.

Product Code	I.D. (mm)	O.D. (mm)	W.P (psi)	Weight (kg/mt)
E05-012	12.5	20.6	50	0.25
E05-016	16.0	23.8	50	0.33
E05-020	20.0	27.0	50	0.40

