

SILICONE HOSE

3 PLY SILICONE RADIATOR HOSE:



Applications For heavy duty pressure connections in hostile engine environments. Resists hardening, cracking, cold leaks, aging, steam and many chemicals. Ideal for extreme temperature and various pressure ranges where high performance levels are required.

Features: Temperature range - 54 oC to 177 oC. Meets or exceeds operating requirements of SAE J20 R1 Class A custom wall, TMC RP303B Class 1 Grade 2 and most OEM truck manufacturers specifications.

Product Code	Burst Pressure (psi)	Imperial Size	Weight (Kg/m)
K01-022	465	7/8"	0.42
K01-025	450	1"	0.48
K01-028	435	1 1/8"	0.54
K01-032	425	1 1/4"	0.6
K01-035	400	1 3/8"	0.65
K01-038	375	1 1/2"	0.71
K01-041	350	1 5/8"	0.77
K01-044	300	1 3/4"	0.83
K01-050	250	2"	0.95
K01-054	235	2 1/8"	1.01
K01-057	225	2 1/4"	1.07
K01-060	210	2 3/8"	1.13
K01-063	200	2 1/2"	1.19
K01-067	200	2 5/8"	1.25
K01-070	200	2 3/4"	1.31
K01-076	200	3"	1.43
K01-083	175	3 1/4"	1.55
K01-088	150	3 1/2"	1.67
K01-095	135	3 3/4"	1.79
K01-100	125	4"	1.90
K01-112	100	4 1/2"	2.14
K01-125	90	5"	2.38



SILICONE HEATER HOSE:

Features: Continuous operating temperature -54 oC to 177 oC. Nylon fiber reinforced. Resistant to coolant additives. Flexfab silicone heater hose is shipped on wooden reels (pictured above) or handy dispenser cartons.

Part No	Imperial Size	Burst Pressure (PSI):
K02-006	1/4" x 1 MT	320
K02-010	3/8" x 1 MT	310
K02-012	1/2" x 1 MT	310
K02-016	5/8" x 1 MT	300
K02-020	3/4" x 1 MT	300
K02-025	1" x 1 MT	250

TURBO CHARGE HOSE 36" LENGTHS:



Applications: Connection between the turbocharger and tech engine. Resists chemicals, steam, ozone, coolants and aging conditions normally found in the engine environment. Red in color.

Product Code	Imperial Size
K04-038	1 1/2"
K04-041	1 5/8"
K04-044	1 3/4"
K04-050	2"
K04-057	2 1/4"
K04-060	2 3/8"
K04-063	2 1/2"
K04-070	2 3/4"
K04-076	3"
K04-088	3 1/2"
K04-100	4"

CONVOLUTED CHARGE AIR HOSE C/W STAINLESS STEEL RINGS:



Applications: For superior connection between engine mounted charge air system components. Ideal for handling slight misalignments and isolating vibration between hose ends.

Part No	Imperial Size	O.D	Burst Pressure (PSI)
K03-001	3" x 6"	3.28	60
K03-002	3 1/2" x 6"	3.73	55
K03-003	4" x 6"	4.23	50
K03-004	4" x 8"	4.23	50
K03-005	4 1/2" x 6"	4.73	45
K03-006	4" x 4 1/2" x 6"	4.23	50

